

ROOF REPAIR SOLUTION

Waterproofing for difficult roof details

IKO Hybritech MS Detail



ROOFMART
IRELAND

A new environmentally friendly, highly-elastic, one-component, liquid waterproofing barrier for the seamless sealing of all flat roofs.

Remove areas around roof glands, skylights, roof windows, chimneys, rainwater drains, inside and outside corners, etc. and all other complex shapes on the roof without the application of heat.



Roof details are easily made 100% waterproof. When dry, an elastic film is formed that absorbs the movements of the substrate and becomes one with the entire surface. Due to its special formulation, it adheres to the most commonly used substrates, dry or slightly damp, without a primer.



Highly elastic



Seamless
waterproof barrier



Adheres to
any substrate



Environmentally
friendly and safe
to use



Easy to apply.
A primer is
not required



Application

For use on the most commonly used building materials, such as bitumen substrates, concrete, brick, wood, PVC, copper, zinc, steel, aluminium, cement render, polyester, etc. Suitable for natural stone, polypropylene (PP) and polythene (PE). When in doubt, test it on a small area first.

How do I prepare the surface?

First remove all dust and grease from the substrate.

How do I use the product?

Roof repair solution provides lasting protection for up to 10 years. The drying time of the resin depends on the relative humidity of the air and ambient temperature.

With relative humidity level of 50% and 20°C IKO Hybritech MS Detail is rainproof after 3 hours and 2 mm of IKO Hybritech MS Detail fully cures in 24 hours.

Apply a first layer of IKO Hybritech MS Detail, using 1 kg/m². Place a piece of IKO polyester Fleece 30 (made from 30 g/m² polyester) on the wet coating, press the fleece into the first layer using a dry roller and make sure that the fleece is fully saturated with IKO Hybritech MS Detail.

There must not be any air bubbles between the first layer and the reinforcement membrane. Make sure that you leave a 5 cm overlap on the edges of the reinforcement fleece. Immediately apply a second layer of IKO Hybritech MS Detail wet on wet, using 0.7 kg/m².

Handy tips

- ✓ Store in a cool (max. 20°C) and frost-free place.
- ✗ Do not apply if the ambient or substrate temperature is below +5°C, above +30°C or during rain or fog.
- ✓ Clean your tools with IKO tech cleaner.
- ✗ Hybritech MS Detailing reacts to humidity. It should not be stirred before or during use; this will activate the drying process in the can. If any of the product remains in the can after use, air will be trapped inside the can when it is sealed. A film will be formed that protects the remaining product from air ingress. It can be used as usual after removing this protective film
- ✓ Consumption is 1,7kg/m² in 2 layers.



DUBLIN NORTH

Unit 502
Northwest Business Park
Ballycoolin
D15 CP3V

T: 01 885 5090
E: dublinnorth@roofmart.ie

DUBLIN SOUTH

Unit 5
Broomhill Business Complex
Tallaght
D24 X270

T: 01 417 9641
E: dublinsouth@roofmart.ie

CORK

Unit 3
South Ring West Business Park
Tramore Road, Cork
T12 FC60

T: 021 431 7903
E: sales@roofmart.ie

BELFAST

2-4 Old Church Road
Newtownabbey
County Antrim
BT36 7LU

T: 028 9086 7079
E: belfast@roofmart.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued. **April 2026.**

WWW.ROOFMART.IE
WWW.ROOFMART.CO.UK