

DAMP PROOFING & TANKING MEMBRANE

Multiple uses for structural waterproofing

IKO Hyload SA Tanking Membrane 1500SA



**ROOFMART
IRELAND**

IKO Hyload Tanking Membrane 1500SA can be used as a fully bonded damp proofing membrane for interior and external below ground waterproofing applications.



Application

IKO Hyload Tanking Membrane 1500SA can be used as a fully bonded damp proofing membrane, as a post applied tanking membrane for external below ground waterproofing applications.

It is classified as a Type A Barrier Membrane that offers protection within a structural waterproofing system designed to be compliant with the guidance of BS8102:2022.



Robust and durable

The product's combination of polymer modified bitumen on a polyethylene carrier makes it a tough and durable material choice



Ease of use

The product is cold applied and does not use specialist tanking equipment, making it a cost effective, low labour application



Applying hyload 1500SA

1. Concrete substrate needs to be clean and dry free from any contaminates.
2. Apply SA bitumen roofing primer to area you wish to cover.
3. Wait for 15-20 mins for the primer to become tacky.
4. Lay the hyload 1500SA vertically down the wall starting at the top, peel off the backing film for about 300mm and adhere to the top of the wall this will hold the roll as you work your way down pushing the material on to the primer as you go to insure a good stick.
5. Insure there is no air bubbles behind the membrane by pushing them to the side.
6. The product also has a self-adhesive overlap ,so remove the film as you work down to create a good bond at the lap.
7. If you are planning on back filling this area, we would recommend hyload protection boards bonded to the hyload 1500SA so that the membrane does not get damaged when filling.

System components

IKO have a range of essential system components, specifically tailored to facilitate the multiple uses of the versatile IKO Hyload SA Tanking Membrane systems. The following represents system components available as part of that range:

- IKOpro SA Bitumen Primer
- IKO Plasdrain Drainage Mats
- IKO Hyload Protection Board
- IKO Flashing Tape
- IKO Hyload Jointing Tape No2
- IKO Hyload Jointing Tape No3
- IKO Hyload Fixing Strips
- IKO Hyload Fixing Pins for Masonry
- IKO Hyload Pre-formed Cloak Units



DUBLIN NORTH

Unit 502
Northwest Business Park
Ballycoolin
D15 CP3V

T: 01 885 5090
E: dublinnorth@roofmart.ie

DUBLIN SOUTH

Unit 5
Broomhill Business Complex
Tallaght
D24 X270

T: 01 417 9641
E: dublinsouth@roofmart.ie

CORK

Unit 3
South Ring West Business Park
Tramore Road, Cork
T12 FC60

T: 021 431 7903
E: sales@roofmart.ie

BELFAST

2-4 Old Church Road
Newtownabbey
County Antrim
BT36 7LU

T: 028 9086 7079
E: belfast@roofmart.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued. **April 2026.**

WWW.ROOFMART.IE
WWW.ROOFMART.CO.UK