

DURABLE ROOF REPAIR

Universal waterproof repair layer

IKO Tanetech Detail



**ROOFMART
IRELAND**

IKO Tanetech Detail is used to realise a waterproof connection to complex roofs and all aspects of flat roofing.

Thanks to its high viscosity, IKO Tanetech Detail doesn't flow down when applied to upstands.



A one-component liquid waterproofing system based on PU. IKO tanetech Detail contains solvents and fibres. The incorporation of special fibres gives the system particularly high elongation and tensile resistance.

- One component: simple and rapid installation
- Proven moisture curing PU technology
- Viscous: does not drip down when applied vertically
- Long lasting repairs for up to 7 years



**Adheres to
any substrate**



**Waterproofs in
any weather**



**Repairs and
renews with 1 coat**



Ready to use



**Reinforced with
synthetic fibres**



Application

For use on various substrates such as bitumen roofing membranes, shingles, slates, tiles, wood, corrugated sheets, aluminium, zinc, lead, PVC (gutters), concrete, masonry, stone, porous tiles, etc.

How do I prepare the surface?

IKO Tanetech Detail can only be applied to a substrate that is clean, dry and free of dust, as well as loose particles. The slope of the substrate must be at least 1:40 fall towards the water drains in order to prevent any water from stagnating. Cracks, blisters, expansion joints and finishes on existing substrate edges must be checked and, if necessary, repaired or replaced.

How do I use the product?

1. Ensure the area to be treated is clean and dry before commencement.
2. If applying to PVC roofing, using IKO tech cleaner is recommended.
3. When the area is clean and dry, apply a Tanetech nonporous primer to the area – this dries in 20 minutes.
4. To ensure a clean edge use masking tape to square off the area to be treated.
5. Apply Tanetech detail liberally over the area – after 10 minutes the masking tape can be removed,
6. After application, if it starts to rain the product will not be affected.

Handy tips

- ✓ Spreads straight from the tin (no need for additional hardeners).
- ✓ Dries in about 4 hours with the humidity in the air.
- ✓ Fibre reinforcement is already present in the tin – so no need for additional reinforcement.
- ✓ Ideal for dressing complex details – as it can be laid vertically without any slippage.
- ✓ As its a liquid waterproofing there is no need for any hot works.
- ✓ After drying, Tanetech detail can be painted over with a waterbased paint if required.



DUBLIN NORTH

Unit 502
Northwest Business Park
Ballycoolin
D15 CP3V

T: 01 885 5090
E: dublinnorth@roofmart.ie

DUBLIN SOUTH

Unit 5
Broomhill Business Complex
Tallaght
D24 X270

T: 01 417 9641
E: dublinsouth@roofmart.ie

CORK

Unit 3
South Ring West Business Park
Tramore Road, Cork
T12 FC60

T: 021 431 7903
E: sales@roofmart.ie

BELFAST

2-4 Old Church Road
Newtownabbey
County Antrim
BT36 7LU

T: 028 9086 7079
E: belfast@roofmart.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued. **April 2026.**

WWW.ROOFMART.IE
WWW.ROOFMART.CO.UK