

WATERPROOFING SOLUTION

Cement based waterproofing for interior and exterior walls and other damp surfaces

IKOpro Cellar Proof



**ROOFMART
IRELAND**

Easy to apply white cement layer for waterproofing of all problematic concrete and masonry walls.

IKOpro CELLAR PROOF specific composition ensures an optimum sealing of all rooms affected by water infiltration and damp. It forms a waterproof moisture barrier on all constructions located partly or fully underground.



IKOpro CELLAR PROOF ensures optimum sealing on the most common porous mineral construction materials such as cement and concrete blocks. As a result, it also forms a unique moisture barrier on floors and walls in sanitary facilities: bathrooms, showers, toilets before the application of decorative finishes.



Can be applied to damp surfaces



Meets the strictest requirements



Optimum sealing on common porous mineral materials



Forms a unique moisture barrier



Application

Both interior and exterior walls: cellars, foundations, ponds, water reservoirs, convection trenches, tunnels, etc.

Apply in a cross pattern with the special Cellar brush at a ratio of 1.5 to 2kg/m², to achieve a thickness of 1mm. After approx. 24 hours, lightly moisten the surface again and apply a second layer (approx. 1mm). Avoid the formation of water drops on the surface when moistening.

Do not mix more of the product than can be applied in approx. 45min (depending on the surrounding temperature) and avoid excessively rapid drying. The surface may need to be moistened in the meantime.

Covers: 1.5 to 2 kg/m² to achieve a thickness of 1mm.

Precautions

Do not apply when room or underground temperature is below 5°C (also applies during hardening). For exterior applications, protect the coating from rain for approx. 24 hours.

If CELLAR PROOF is used to waterproof a drinking water reservoir, swimming pool or fish pond, the hardened coating must be washed with a salt solution (brine, 12.5% salt in water). Leave the brine solution on the floor and walls overnight. Then clean the surface with clean water. Repeat this process until the required pH level is achieved.

Handy tips

- ✓ Clean tools in water, immediately after use.
- ✓ Store in a protected, moisture and frost-free place to guarantee a storage time of 1 year in unopened packaging.
- ✓ The presence of sulphate (salts) in bricks can cause potential adhesion problems. Treat your cellar when the water pressure is at its lowest in order to give the coating time to fully harden.
- ✓ Ensure sufficient ventilation during the hardening process. During hot and humid weather, condensation may form in poorly ventilated cellars.



DUBLIN NORTH

Unit 502
Northwest Business Park
Ballycoolin
D15 CP3V

T: 01 885 5090
E: dublinnorth@roofmart.ie

DUBLIN SOUTH

Unit 5
Broomhill Business Complex
Tallaght
D24 X270

T: 01 417 9641
E: dublinsouth@roofmart.ie

CORK

Unit 3
South Ring West Business Park
Tramore Road, Cork
T12 FC60

T: 021 431 7903
E: sales@roofmart.ie

BELFAST

2-4 Old Church Road
Newtownabbey
County Antrim
BT36 7LU

T: 028 9086 7079
E: belfast@roofmart.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued. **April 2026.**

WWW.ROOFMART.IE
WWW.ROOFMART.CO.UK