

EPDM Rubber Roof

Your made-to-measure roof in one piece

Roofmart EPDM RUBBER



ROOFMART
IRELAND

Roofmart EPDM RUBBER allows you to create a custom roof from a one layer application for all flat and slightly sloping roofs.

EPDM roofing is very easy to install without a burner and is ideal for any DIY enthusiasts.



Useful facts

The current system is intended for flat and slightly sloping roofs up to a maximum slope of 5°.

With a greater slope of up to max. 45° and a roof area of max. 10 m² (due to slipping), the foil must be mechanically attached to the top or to be extended over the ridge of the roof. In connection with a smooth rainwater evacuation, the adhesive grooves must be applied from top to bottom

- Good resistance to temperature fluctuations and high temperature stability (-40°C to +120°C)
- Recyclable, environmentally neutral.



Crack, break,
shrink & rot free



Low maintenance



Good resistance
to temperature
fluctuations



Suitable for
household use



How do I use the product?

1. Place the EPDM roll on the roof surface and let it rest for a few hours, making sure the EPDM is evenly distributed. Then fold the foil back in half.
2. Apply the EPDM Bonding Adhesive to the exposed part of the roof surface, up to 15 cm from the roof upstand or wall. Spread the adhesive by pouring it out while making a hose-like movement (maximum 8 cm gap). For small surfaces (<15 m²) you can apply the EPDM in stripes. Repeat this for the other side. Use EPDM special primer when you place EPDM on an existing roof covering or a concrete surface.
3. Glue the edges with Contact adhesive on upstands, apply the glue to all surfaces. When the glue is dry to the touch, carefully fold the EPDM into place and press with a pressure roller.
4. Fold the EPDM in the corners into a cone, then fold the EPDM flat over the roof edge and finish with roof edge profiles. You can also use pre-formed EPDM corner pieces.
5. Seal the overlapping areas with EPDM primer / tape on all Overlaps. Fold the EPDM back 10 cm at the seam. Keep the outer 2 cm free and apply glue to the remaining 8 cm of this flap with a brush. Fold the EPDM back carefully and press firmly with a hand roller. Make the seam even more waterproof by gluing the remaining 2 cm strip with EPDM lap sealer to the Seams. Press firmly with a pressure roller and ensure that glue comes from under the seam for extra waterproofing.
6. Finish roof details such as chimneys or drains with Detailing membrane and bond this with lap sealer and a mastic gun. Determine the location where a rainwater drain will be and cut this section away. Always use pre-formed EPDM pieces and pre-formed drains. Make sure that glue comes from under the seams for extra waterproofing.

All EPDM Accessories are available from Roofmart Ireland.

Handy tips & facts

Easy to install without a burner and is ideal for any DIY enthusiasts.

- ✓ PDM membrane made from one piece
- ✓ Flexible and pleasantly elastic
- ✓ Suitable for both professionals and DIY enthusiasts
- ✓ Root resistant, suitable for green roofs
- ✗ Do not apply at ambient and subsurface temperatures lower than +5°C. Store frost-free.



DUBLIN NORTH

Unit 502
Northwest Business Park
Ballycoolin
D15 CP3V

T: 01 885 5090
E: dublinnorth@roofmart.ie

DUBLIN SOUTH

Unit 5
Broomhill Business Complex
Tallaght
D24 X270

T: 01 417 9641
E: dublinsouth@roofmart.ie

CORK

Unit 3
South Ring West Business Park
Tramore Road, Cork
T12 FC60

T: 021 431 7903
E: sales@roofmart.ie

BELFAST

2-4 Old Church Road
Newtownabbey
County Antrim
BT36 7LU

T: 028 9086 7079
E: belfast@roofmart.co.uk

Whilst every care is taken to see that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification or application details or otherwise have taken place since this literature was issued. **April 2026.**

WWW.ROOFMART.IE
WWW.ROOFMART.CO.UK